

# EC5-1721CLDNA

5.25" SBC with Low-power CPU/LVDS/VGA/DVI/LAN/Audio



3

Slot  
CPU/SBC/  
Motherboard



## FEATURES

- 533/400MHz system bus, supporting VIA C7 and VIA Eden™ processor (onboard C7 1.5GHz)
- CX700M south and north bridge two-in-one single chipset
- 2 x 10/100Mbps Ethernet port

## SPECIFICATIONS

**Product Type:** 5.25" embedded SBC  
**Processor:** 533/400MHz system bus, supporting VIA C7 and VIA Eden™ processor (onboard C7 1.5GHz)  
**Chipset:** CX700M south and north bridge two-in-one single chipset  
**Memory:** Onboard DDR II 512M memory, one SODIMM DDRII slot  
**BIOS:** AMI BIOS, supporting the function of ACPI advanced power supply management  
**Onboard Video:** 1 x VGA port, 1 x LVDS port, 1 x DVI port.  
**Network:** 2 x 10/100Mbps Ethernet port  
**Onboard Audio:** AC' 97 audio controller  
**HDD Interface:** 1 x ATA/100/66/33IDE channel, 2 x SATA port  
**I/O Interface:** 4 x RS-232, one of which supports RS232/422/485, 1 x parallel port, 1 x IrDA/Infrared interface, 4 x USB 2.0 port, 1 x PS/2 port  
**Flash Storage:** 1 x CF interface  
**Expansion Bus:** 2 x PCI slot  
**Operating Temperature:** 0°C~60°C  
**Operating Humidity:** 5%~90%, non-condensing