

HSC-1723CLD2NA

Half-size ISA-bus CPU Card with VIA CPU/RAM and VGA/LVDS/2 LAN/SSD



3

Slot
CPU/SBC/
Motherboard



SPECIFICATIONS

Product Type: Half-size ISA bus

Processor: 533/400MHz system bus, supporting VIA C7 and VIA Eden™ processor (onboard C7 1.5GHz)

Chipset: CX700M south and north bridge two-in-one single chipset

Memory: Onboard 512M DDR II memory

BIOS: AMI BIOS supports the function of ACPI advanced power supply management

Onboard Video: 1 x VGA port, 1 x LVDS port

Network: 3 x 10/100M Ethernet port, one of which is routed out with pins

Onboard Audio: ALC260 audio controller

HDD Interface: 1 x ATA/100/66/33IDE channel, 2 x SATA interface

I/O Interface: 6 x RS-232, one of which supports RS232/422/485

1 x parallel port

4 x USB 2.0 port

1 x PS/2 KB/MS interface

1 x CPU fan port (standby)

Quadruple input and quadruple output

Indicator Lamp: Onboard power and HDD running indicator lamp

Flash Storage: 1 x CF slot

Watchdog Timer: Software programmable supports 1~255 sec./min. System reset/interrupt

Hardware Monitor: Monitors CPU voltage, temperature and fan speed.

Power Supply: +5V, +12V, supporting AT/ATX

Dimensions: 185mm x 122mm

Operating Temperature: 0°C~60°C

Operating Humidity: 5%~90%, non-condensing

FEATURES

- On-board VIA C7 and VIA Eden™ processor
- CX700M chipset
- Onboard 512M DDR2 memory
- VGA and LVDS supported
- ALC260 audio controller